




TECHNICAL DATA SHEET

Type no.	560 10		
Article no.	010560100101		
Standards	DIN EN 50342, DIN IEC 60095-2		
Application	Starter battery		
Electrical data			
Rated voltage	12V		
Rated capacity	60 Ah (K20)		
Cold start current	675 A (EN)		
Dimensions and weights			
Box			
Length max.			248mm
Width max.			178mm
Box height max.			184mm
Total height max.			184mm
Battery weight	Ca. 15,5 kg (+/- 5 %)		
Electrolyte density	Approx. 1,28 kg/l		
Electrolyte	Diluted sulphuric acid		
Items/pallet	72		
Pallet ID	Euro palett		
Items per layer	16		
Features			
Base hold-down	B7		
Layout	1		
Terminal	5		
Separator	PE bag separator		
Degassing	Battery with central degassing		
Flame arrester	Not available		
Maintenance 1)			
Water consumption	< 1g/Ah		
Refill water	Distilled or demineralised (DIN 43530)		
Self-discharge	Approx. 3 % per month		
Charging current	Approx. 1/10 of the rated capacity		
Charging voltage 2)	max. 14,8 V		

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

Document DBTBAT00325 prepared on 2013-09-19 ; Rights relating to changes and errors retained.
original