



# TECHNICAL DATA SHEET

Type no.	625 13	
Article no.	010625130101	
Standards	DIN EN 50342-1, 50342-2	
Application	Starter battery	
<b>Electrical data</b>		
Rated voltage	12V	
Rated capacity	125 Ah (K20)	
Cold start current	760 A (EN)	
<b>Dimensions and weights</b>		
Box	A98COMPACT	
Length max.	345mm	
Width max.	172mm	
Box height max.	260mm	
Total height max.	283mm	
Battery weight	Ca. 32,5 kg (+/- 5 %)	
Electrolyte density	Approx. 1,28 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	36	
Pallet ID	Euro pallet	
Items per layer	12	
 Symbolpicture		
<b>Features</b>		
Base hold-down	B00	
Layout	1	
Terminal	1	
Separator	PE bag separator	
Degassing	Battery with single degassing	
Flame arrester	Not integrated	
<b>Maintenance 1)</b>		
Water consumption	> 4g/Ah	
Refill water	Distilled or demineralised (DIN 43530)	
Self-discharge	Approx. 9 % per month	
Charging current	Approx. 1/10 of the rated capacity	
Charging voltage 2)	max. 13,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge

1DocumentDBTBAT00339prepared on 2015-07-01 ; Rights relating to changes and errors retained.  
original