

**Professional booster pack with integrated charger, designed for starting vehicles with liquid electrolyte.**



### High performance booster

Equipped with a **high tech** lead battery (Starting current 1V/c: 830A, peak current 3100A), the Gyspack 810 is the ideal unit to start any vehicle up to vans, light duty vehicles, tractors and trucks.

### Works on-site

Light (15kg) and robust, the Gyspack 810 can be **easily carried on site without any effort.**

### Safety

- ✓ Audible and visual alarm to protect against inadvertent polarity reversal.
- ✓ Equipped with a circuit breaker to protect the vehicle against overvoltage and short-circuits. No sparks when the clamps are being connected.
- ✓ Long 1.80m starting cables with high quality insulated clamps for access to the vehicle.
- ✓ **200A** externally visible and accessible fuses to protect against handling errors or defective vehicles.




### Complete charge without supervision

- ✓ A major feature of this product is the high specification WUoU multi-stage charger integrated within the unit. **Its advanced 'floating mode' allows the Gyspack being left on charge permanently (no supervision required).**











- ✓ Visual LED charge status indicator.

### Memory save mode

- ✓ Additional feature of cigar-lighter connection to maintain or save vehicle settings (15 A fuse) while changing the battery.



CE - EN 60335-2-29

		START				CHARGEUR INSIDE 	PROTECTION  		POWER OUT  				
	I 1V/C	Cranking CC	Peak Battery										
	12V HAWKER 30Ah	830A	1700A	3100A	•	3A	•	•	12V DC	15A	2x1,80m ø 35 mm²	18x38x31	16,6